

SAFETY DATA SHEET

Denaturerad ETANOL 99% (denaturerad med Butanol)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Denaturerad ETANOL 99% (denaturerad med Butanol)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Solvent - Industrial purposes.

Relevant identified uses of the substance or mixture (REACH)

No special

▼ Uses advised against

No special

1.3. Details of the supplier of the safety data sheet

Company and address

Solveco AB

Tallbacksgatan 10
S-195 72 Rosersberg
Sverige
T: +46 (0)8 732 72 75
F: +46 (0)8 732 72 76
<http://www.solveco.se>

Contact person

Habib Hourani

E-mail

info@solveco.se

SDS date

2020-06-16

SDS Version

2.0

Date of previous version

2019-10-01 (1.0)

▼ 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.

Eye Dam. 1; H318, Causes serious eye damage.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Highly flammable liquid and vapour.
Causes serious eye damage.

Safety statement(s)

▼ General

-

Prevention

P280, Wear eye protection.
P210, Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response

P305+P351+P338, IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310, Immediately call a POISON CENTER/doctor.

Storage

P403+P235, Store in a well-ventilated place. Keep cool.

Disposal

P501, Dispose of contents/container to an approved waste disposal plant.

▼ Hazardous substances

butan-1-ol

2.3. Other hazards

Additional labelling

Not applicable

▼ Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

SECTION 3: Composition/information on ingredients

▼ 3.2 Mixtures

Product/Ingredient name	Identifiers	% w/w	Classification	Note
Ethanol	CAS No.: 64-17-5 EC No.: 200-578-6 REACH No.: Index No.: 603-002-00-5	99%	Flam. Liq. 2, H225 Eye Irrit. 2, H319	
butan-1-ol	CAS No.: 71-36-3 EC No.: 200-751-6 REACH No.: Index No.: 603-004-00-6	≤ 4%	Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

No special

SECTION 4: First aid measures

▼ 4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

▼ Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

▼ Eye contact

Upon irritation of the eye: Remove contact lenses. Flush eyes with plenty of water or salt water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

▼ 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

▼ Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.

▼ 5.2. Special hazards arising from the substance or mixture

Fire will result in dense black smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Avoid inhalation of vapours from spilled material.

▼ 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste.

See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

▼ 7.1. Precautions for safe handling

Protect electrical equipment in accordance with current standards. To divert static electricity during transmission, containers must be grounded and connected by wire with the receiving containers. Do not use spark-forming tools.

Avoid static electricity.

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating]equipment.

Use non-sparking tools.

Smoking, drinking and consumption of food is not allowed in the work area.

See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Take action to prevent static discharges.

Storage temperature

Dry, cool and well ventilated

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

▼ 8.1. Control parameters

—
Ethanol

Long term exposure limit (8 hours): 1000 ppm

Long term exposure limit (8 hours): 1920 mg/m³

—
butan-1-ol

Short term exposure limit (15 minutes): 50 ppm

Short term exposure limit (15 minutes): 154 mg/m³

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020)

DNEL

No data available

▼ PNEC

No data available

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, eating and drinking are not allowed in the work premises

▼ Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

▼ Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above).

Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended.

Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure


No specific requirements

Individual protection measures, such as personal protective equipment


Generally

Use only CE marked protective equipment.


▼ Respiratory Equipment

Work situation	Recommended Filter type	Class	Colour	Standards	
If ventilation at the work place is insufficient, use a half- or full mask with an appropriate filter or an air-supplied breathing apparatus.	A	-	Brown	EN14387	

▼ Skin protection

Work situation	Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	-	

▼ Hand protection

Work situation	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
	Butyl	-	-	EN374-2, EN374-3, EN388, EN421	

Work situation	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
	Nitrile	-	-	EN374-2



▼ Eye protection

Work situation	Recommended	Standards
	Use face protection or safety glasses with side shields.	EN166



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form

Liquid

Colour

Colourless

Odour

Characteristic

Odour threshold (ppm)

~350

▼ pH

Testing not relevant or not possible due to nature of the product.

Density (g/cm³)

0.79

▼ Viscosity

Testing not relevant or not possible due to nature of the product.

Phase changes

Melting point (°C)

-114

Boiling point (°C)

78.00 °C

Vapour pressure

5.90 kPa (20.00 °C)

Vapour density

1.59

▼ Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product.

▼ Evaporation rate (n-butylacetate = 100)

Testing not relevant or not possible due to nature of the product.

Data on fire and explosion hazards

Flash point (°C)

12.00 °C

▼ Ignition (°C)

Testing not relevant or not possible due to nature of the product.

Auto flammability (°C)

425 °C

Explosion limits (% v/v)

3.30 - 19.00 v/v%

▼ Explosive properties

Testing not relevant or not possible due to nature of the product.

▼ Oxidizing properties

Testing not relevant or not possible due to nature of the product.

Solubility

Solubility in water

Soluble

n-octanol/water coefficient

-0.32

▼ Solubility in fat (g/L)

Testing not relevant or not possible due to nature of the product.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

▼ Acute toxicity

Product/Ingredient name	Species	Test	Route of exposure	Result
Ethanol	Rabbit	LD50	Dermal	>20000.00 mg/kg
Ethanol	Rat	LD50	Oral	6200.00 mg/kg
Ethanol	Rat	LC50 (4 hours)	Inhalation	124.70 mg/l

▼ Skin corrosion/irritation

Based on available data, the classification criteria are not met.

▼ Serious eye damage/irritation

Based on available data, the classification criteria are not met.

▼ Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

▼

▼ Germ cell mutagenicity

Based on available data, the classification criteria are not met.

▼ Carcinogenicity

Based on available data, the classification criteria are not met.

▼ Reproductive toxicity

Based on available data, the classification criteria are not met.

▼ STOT-single exposure

Based on available data, the classification criteria are not met.

▼ STOT-repeated exposure

Based on available data, the classification criteria are not met.

▼ **Aspiration hazard**

Based on available data, the classification criteria are not met.

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

▼ **Other information**

Ethanol has been classified by IARC as a group 1 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

Product/Ingredient name	Species	Test	Duration	Result
Ethanol	Fish (Pimephales promelas)	LC50	96 hours	13480.00 mg/l
Ethanol	Algae (Scenedesmus subspicatus)	IC50	7 days	5000.00 mg/l
Ethanol	Daphnia (Daphnia magna)	EC50	48 hours	5400.00 mg/l
Ethanol	Algae	IC50	72 hours	>10.9 mg/l

12.2. Persistence and degradability

Product/Ingredient name	Biodegradability	Test	Result
Ethanol	Yes	BOD5/COD	0.4 - 0.8

▼ **12.3. Bioaccumulative potential**

Product/Ingredient name	Potential bioaccumulation	LogPow	BCF
Ethanol	No	No data available	< 10

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

No special

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

EWC code

Not applicable

Specific labelling

Not applicable

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 - 14.4

This product is within scope of the regulations of transport of dangerous goods.

▼ ADR/RID

UN no.	Proper Shipping Name	Class	PG	Tunnel restriction code
1170	ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	3	II	2 (D/E)

▼ IMDG

UN no.	Proper Shipping Name	Class	PG	EmS
1170	ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	3	II	F-E, S-D

▼ IATA

Not applicable

▼ "MARINE POLLUTANT"

No

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

▼ 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

▼ Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

▼ Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

▼

P5c

▼

▼ Additional information

Not applicable

▼ Sources

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

The Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

Regulation (EC) 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

▼ Full text of H-phrases as mentioned in section 3

- H225, Highly flammable liquid and vapour.
- H319, Causes serious eye irritation.
- H226, Flammable liquid and vapour.
- H302, Harmful if swallowed.
- H315, Causes skin irritation.
- H318, Causes serious eye damage.
- H335, May cause respiratory irritation.
- H336, May cause drowsiness or dizziness.

Abbreviations and acronyms

- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- CAS = Chemical Abstracts Service
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- CSA = Chemical Safety Assessment
- CSR = Chemical Safety Report
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EINECS = European Inventory of Existing Commercial chemical Substances
- ES = Exposure Scenario
- EUH statement = CLP-specific Hazard statement
- EWC = European Waste Catalogue
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IARC = International Agency for Research on Cancer (IARC)
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- OECD = Organisation for Economic Co-operation and Development
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
- RRN = REACH Registration Number
- SVHC = Substances of Very High Concern
- STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
- STOT-SE = Specific Target Organ Toxicity - Single Exposure
- TWA = Time weighted average
- UN = United Nations
- UVCB = Complex hydrocarbon substance
- VOC = Volatile Organic Compound
- vPvB = Very Persistent and Very Bioaccumulative

Additional information

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

The classification of the mixture in regard of physical hazards has been based on experimental data.

[The safety data sheet is validated by](#)

Habib Hourani

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.