

SAFETY DATA SHEET

ECOSOLV A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

ECOSOLV A

▼ REACH registration number

-

▼ Other means of identification

-

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Solvent - Industrial purposes.

▼ Relevant identified uses of the substance or mixture (REACH)

No special

▼ Uses advised against

No special

1.3. Details of the supplier of the safety data sheet

Company and address

Solveco AB

Tallbacksgatan 10

S-195 72 Rosersberg

Sverige

T: +46 (0)8 732 72 75

F: +46 (0)8 732 72 76

<http://www.solveco.se>

Contact person

Habib Hourani

E-mail

info@solveco.se

SDS date

2020-02-24

SDS Version

2.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

▼ 2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.

Eye Irrit. 2; H319, Causes serious eye irritation.

STOT SE 3; H336, May cause drowsiness or dizziness.

▼
2.2. Label elements▼
Hazard pictogram(s)


Signal word

Danger

Hazard statement(s)

Highly flammable liquid and vapour.
 Causes serious eye irritation.
 May cause drowsiness or dizziness.

Safety statement(s)
General
Prevention

P280, Wear eye protection.

P210, Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response

P337+P313, If eye irritation persists: Get medical advice/attention.

P370+P378, In case of fire: Use carbonic acid/water mist/carbon dioxide/alcohol-resistant foam to extinguish.

Storage

P403+P235, Store in a well-ventilated place. Keep cool.

Disposal

P501, Dispose of contents/container to an approved waste disposal plant.

▼ Hazardous substances

Isopropanol

2.3. Other hazards
▼ Additional labelling

Not applicable

▼ Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

SECTION 3: Composition/information on ingredients
▼ 3.2 Mixtures

Product/Ingredient name	Identifiers	% w/w	Classification	Note
Ethanol	CAS No.: 64-17-5 EC No.: 200-578-6 REACH No.: Index No.: 603-002-00-5	60 - 70%	Flam. Liq. 2, H225 Eye Irrit. 2, H319	
Isopropanol	CAS No.: 67-63-0 EC No.: 200-661-7 REACH No.: Index No.: 603-117-00-0	30 - 40%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

No special

SECTION 4: First aid measures

▼ 4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

▼ Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

▼ Eye contact

Upon irritation of the eye: Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 5 minutes and continue until irritation stops. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

▼ 4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

▼ 5.1. Extinguishing media

Extinguish fire with carbonic acid, powder or foam. Do not use water, as this will spread the fire.

▼ 5.2. Special hazards arising from the substance or mixture

Fire will result in dense black smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

▼ 6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid inhalation of vapours from spilled material.

▼ 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste.

See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

▼ 7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating]equipment.

Use non-sparking tools.

The product should be tested for peroxides before distillation or evaporation and tested for peroxide formation or discarded after 1 year.

Peroxide formation may be present anywhere in the container, including the sides, bottom, exterior and threaded cap. Peroxide formation in ppm concentrations may not be visually observable and must be identified through the use of appropriate testing procedures. If any of the following conditions exist, the material may be explosively unstable and will require stabilization prior to use:

1. Material appears to be degraded and or contaminated.
2. Material appears to be discolored.
3. Deterioration or distortion of storage container.
4. Thermal shock (sunlight).
5. Age of material exceeds recommended storage time.

Smoking, drinking and consumption of food is not allowed in the work area.

See section on 'Exposure controls/personal protection' for information on personal protection.

▼ 7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container.

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Take action to prevent static discharges.

Storage temperature

Dry, cool and well ventilated

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

▼ 8.1. Control parameters

—

According to EC-Regulation 2015/830

Ethanol

Long term exposure limit (8 hours): 1000 ppm
 Long term exposure limit (8 hours): 1920 mg/m³

—

Isopropanol

Long term exposure limit (8 hours): 400 ppm
 Long term exposure limit (8 hours): 999 mg/m³
 Short term exposure limit (15 minutes): 500 ppm
 Short term exposure limit (15 minutes): 1250 mg/m³

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.

▼ DNEL

Product/Ingredient name	DNEL	Route of exposure	Duration
Isopropanol	500 mg/m ³	Inhalation	Long term – Systemic effects
Isopropanol	888 mg/kg kroppsvikt	Dermal	Long term – Systemic effects - Workers

▼ PNEC

Product/Ingredient name	PNEC	Route of exposure	Duration of Exposure
Isopropanol	28 mg/kg	Soil	No data available
Isopropanol	140,9 mg/L	Freshwater	No data available
Isopropanol	552 mg/kg	Freshwater sediment	No data available
Isopropanol	140,9 mg/L	Marine water	No data available
Isopropanol	552 mg/kg	Marine water sediment	No data available
Isopropanol	2251 mg/L	Sewage Treatment Plant	No data available
Isopropanol	140,9 mg/L	Intermittent release	No data available

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, eating and drinking are not allowed in the work premises

▼ Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of an exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements


Individual protection measures, such as personal protective equipment

According to EC-Regulation 2015/830


Generally

Use only CE marked protective equipment.



Respiratory Equipment

Work situation	Recommended Filter type	Class	Colour	Standards	
If ventilation at the work place is insufficient, use a half- or full mask with an appropriate filter or an air-supplied breathing apparatus.	A	-	Brown	EN14387	


Skin protection

Work situation	Recommended	Type/Category	Standards	
	Dedicated work clothing should be worn.	-	-	

▼ Hand protection

Work situation	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
	Nitrile	-	-	EN374-2	
	Butyl	-	-	EN374-2, EN374-3, EN388, EN421	

Eye protection

Work situation	Recommended	Standards	
	Use face protection or safety glasses with side shields.	EN166	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

▼ Form

Liquid

▼ Colour

Colourless

▼ Odour

Characteristic

▼ Odour threshold (ppm)

Testing not relevant or not possible due to nature of the product.

▼ pH

Testing not relevant or not possible due to nature of the product.

▼ Density (g/cm³)

0.78

▼ Viscosity

Testing not relevant or not possible due to nature of the product.

Phase changes

▼ Melting point (°C)

Testing not relevant or not possible due to nature of the product.

Boiling point (°C)

~ 78 °C

(CAS: 64-17-5)

Vapour pressure

5.90 kPa (20.00 °C)

(CAS: 64-17-5)

▼ Vapour density

Testing not relevant or not possible due to nature of the product.

▼ Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product.

▼ Evaporation rate (n-butylacetate = 100)

Testing not relevant or not possible due to nature of the product.

Data on fire and explosion hazards

Flash point (°C)

~ 12.0 °C

(CAS: 67-63-0)

▼ Ignition (°C)

Testing not relevant or not possible due to nature of the product.

▼ Auto flammability (°C)

Testing not relevant or not possible due to nature of the product.

▼ Explosion limits (% v/v)

2.00 - 19.00 v/v%

▼ Explosive properties

Testing not relevant or not possible due to nature of the product.

▼ Oxidizing properties

Testing not relevant or not possible due to nature of the product.

Solubility

▼ Solubility in water

Soluble

n-octanol/water coefficient

-0.32

(CAS: 64-17-5)

▼ Solubility in fat (g/L)

Testing not relevant or not possible due to nature of the product.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information
11.1. Information on toxicological effects
▼ Acute toxicity

Product/Ingredient name	Species	Test	Route of exposure	Result
Ethanol	Rat	LD50	Oral	6200.00 mg/kg
Ethanol	Rat	LC50 (4 hours)	Inhalation	124.70 mg/l
Ethanol	Rabbit	LD50	Dermal	>20000.00 mg/kg
Isopropanol	Rat	LD50	Oral	4396.00 mg/kg
Isopropanol	Rat	LC50 (4 hours)	Inhalation	46.5-72.0 mg/l
Isopropanol	Rabbit	LD50	Dermal	12800.00 mg/kg

▼ Skin corrosion/irritation

Based on available data, the classification criteria are not met.

▼ Serious eye damage/irritation

Causes serious eye irritation.

▼ Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.


▼ Germ cell mutagenicity

Based on available data, the classification criteria are not met.

▼ Carcinogenicity

Based on available data, the classification criteria are not met.

▼ Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

▼ STOT-repeated exposure

Based on available data, the classification criteria are not met.

▼ Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

▼ Other information

Ethanol has been classified by IARC as a group 1 carcinogen.

Isopropanol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information
▼ 12.1. Toxicity

Product/Ingredient	Species	Test	Duration	Result
--------------------	---------	------	----------	--------

According to EC-Regulation 2015/830

name				
Ethanol	Fish (Pimephales promelas)	LC50	96 hours	13480.00 mg/l
Ethanol	Algae	IC50	72 hours	>10.9 mg/l
Ethanol	Daphnia (Daphnia magna)	EC50	48 hours	5400.00 mg/l
Ethanol	Algae (Scenedesmus subspicatus)	IC50	7 days	5000.00 mg/l
Isopropanol	Fish	LC50	96 hours	4200.00 mg/l
Isopropanol	Algae (Scenedesmus subspicatus)	IC50	96 hours	>1000.00 mg/l
Isopropanol	Daphnia	EC50	48 hours	13299.00 mg/l

12.2. Persistence and degradability

Product/Ingredient name	Biodegradability	Test	Result
Ethanol	Yes	BOD5/COD	0.4 - 0.8
Isopropanol	Yes	OECD 301 C (Modified MITI Test)	84 %

▼ 12.3. Bioaccumulative potential

Product/Ingredient name	Potential bioaccumulation	LogPow	BCF
Ethanol	No	No data available	< 10
Isopropanol	No	No data available	No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

No special

SECTION 13: Disposal considerations

▼ 13.1. Waste treatment methods

To the extent the material has not been subject to regular tests of peroxide formation the waste shall be treated as explosive waste.

Product is covered by the regulations on hazardous waste.

EWC code

Not applicable

Specific labelling

Not applicable

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

14.1 - 14.4

This product is within scope of the regulations of transport of dangerous goods.

▼ADR/RID

UN number	Proper Shipping Name	Class	Packing group	Tunnel restriction code
1987	ALCOHOLS, N.O.S.	3	II	2 (D/E)

▼IMDG

UN number	Proper Shipping Name	Class	Packing group	EmS
1987	ALCOHOLS, N.O.S.	3	II	F-E, S-D

▼IATA

Not applicable

▼Marine pollutant

No

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

▼Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances:



P5c



Additional information

Not applicable

▼Sources

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

The Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

Regulation (EC) 1907/2006 (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVCB = Complex hydrocarbon substance
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

In accordance with Regulation (EC) No. 1272/2008 (CLP) the evaluation of the classification of the mixture is based on:

The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

The classification of the mixture in regard of physical hazards has been based on experimental data.

The safety data sheet is validated by

Habib Hourani

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.